



2009 Scheduled Maintenance Intervals

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95	35/75/115
Kilometers (in thousands)	8/40/70/100/130/160/200	25/85/145	55/115/175
Engine Oil/Oil Filter – change oil and replace filter	•	•	•
Wiper Blades – check condition and replace if necessary	•	•	•
Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary	•	•	•
Tires and Spare – check for wear and damage, check pressure	•		115K only
 check for wear and damage, check pressure and renewal date of tire set (where applicable) 		•	35K and 75K only
AdBlue Fluid – fill completely with fresh fluid (23 liters)	Audi Q7 3.0L TDI only	Audi Q7 3.0L TDI only	Audi Q7 3.0L TDI only
Tires – rotate	SK only		
Service Reminder Display – reset	•	•	•
Brake System – check for damage, leaks, pad thickness, fluid level	•	•	•
Cooling System – check level, add if necessary		•	•
Exhaust System – check for damage, leaks		•	•
Engine On-Board Diagnostics – check fault memory		 A3, A4 Cabriolet, S4, A6, S6, A8 and S8 only 	 A3, A4 Cabriolet, S4, A6, S6, A8 and S8 only
Engine Compartment – check for leaks		•	•
Battery - check and replace if necessary		•	
Dust and Pollen Filter - replace		•	•
Automatic Transmission and Final Drive - check for leaks		•	•
Manual Transmission and Final Drive - check for leaks		•	0
Haldex Clutch - change oil		-	A3 and TT only
-		 A3, A4 Cabriolet, S4, A6, S6, 	AS and 11 only
Front Axle – check for excessive play, check dust seals on ball joints and tie rod ends		A8 and S8 only	
Lights – check all lights, check headlight adjustment		A8 and S8 only	A3, A4 Cabriolet, S4, A6, S6, A8 and S8 only
Drive Shaft Boots – check		•	•
Front Sunroof Drains (where applicable) – open sunroof to check front water drain and clean if necessary (U.S. only)			•
Plenum Panel – remove cover to plenum panel to check water drains and clean if necessary			except A3 and Q5
Doors – lubricate doors, check straps and hood latch		A8 and S8 only	except A8 and S8
Spark Plugs – replace at 35,000 miles or 3 years, whichever occurs first. Then, every 40,000 miles or 3 years, whichever occurs first.			 35K, 75K and 115K: A4 Sedan 2.0 (engine code CAEB), A5 2.0L TFS A3 3.2L, TT 3.2L, TTS and A8 6.0l
 replace at 55,000 miles or 6 years, whichever occurs first. Then, every 60,000 miles or 6 years, whichever occurs first. 		 55K only: except A4 Sedan 2.0L TFSI (engine code CAEB), A5 2.0L TFSI, A3 3.2L, TT 3.2L, TTS and A8 6.0L 	
Continuously Variable Transmission (multitronic) – change ATF			•
Power Steering Fluid – check, add if necessary			•
Air Cleaner – clean housing, replace filter element		 55K only: except Audi Q7 4.2L and A8 6.0L 	 35K only: A8 6.0L only; 75K only: Audi Q7 4.2L, A8 6.0L only; 115K only: A8 6.0L only
Ribbed V Belt and Tensioner – check condition and replace if necessary		Audi R8 only	115K only: A8 6.0L only Audi Q7 3.6L, A8 6.0L, Audi R8 c
Ribbed V Belt – replace		Additionity	75K only: S4 only
- check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary.			75K only: V6 FSI, V6 TFSI (rear b 2.0L TFSI, 5.2L FSI, 4.2L V8 FSI
- replace only the V belt for the compressor drive			75K only: 3.0L TFSI only
Snow Screen for Air Cleaner - clean		A4, A5, S5 and A6 only	A4, A5, S5 and A6 only
Underbody - check for damage and leaks		• 84, 85, 55 and 80 only	A4, A5, 55 and A0 only
Road Test – check braking, kick-down, steering, electrical, heating and ventilation systems, air conditioning, ASL Automatic Shift Lock and power accessories		•	•
Rear Lid Hinges – lubricate		A8 and S8 only	A8 and S8 only
Horn – check function		• To uno 55 only	O STATE SO OTHY
Brake Discs – check thickness		,	•
Lights – check all lights via instrument cluster. Check license plate light from the rear			
of the vehicle			Audi Q7, A4, S4, Audi Q5, TT, A5, S5 and Audi R8 only
Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			
DSG/S Tronic – change oil and replace filter element			A3 and TT only
Fuel Filter – remove water		Audi Q7 3.0L TDI only	
- replace			Audi Q7 3.0L TDI only
Diesel Particle Filter (DPF) – check ash content within the DPF. Replace DPF with an ash content greater than or equal to .46 liters.	■ 125K only: Audi Q7 3.0L TDI only		

Cloth Top – check function and rollover protection every 2 years regardless of mileage (Audi A4/S4 Cabriolet and A5/S5 Cabriolet only).

At 110K miles (175,000 km) replace timing belt on Audi TT 2.0L with front-wheel drive, Audi TTS and A4 Cabriolet 2.0T only. Check condition of timing belt tensioning system, dampening pulleys, and idler pulleys and replace if necessary (Audi TT 2.0T with front-wheel drive, Audi TTS and A4 Cabriolet 2.0T only).

Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.