



2010 Scheduled Maintenance Intervals

	0//0/II0/II0//00//00/		
Kilometers (in thousands)	8/40/70/100/130/160/190	25/85/145	55/115/175
Engine Oil/Oil Filter – change oil and replace filter	•	•	•
AdBlue Fluid – fill completely with fresh fluid (maximum capacity: 23 liters) and	Audi Q7 3.0L TDI only	Audi Q7 3.0L TDI only	Audi Q7 3.0L TDI only
adapt learned values for AdBlue tank under guided fault finding after filling fluid			
Cooling System – check level, add if necessary		•	•
Engine On-Board Diagnostics – check fault memory		A3, A6, S6, A8 only	A3, A6, S6, A8 only
Engine Compartment – check for leaks		•	•
Battery – check and replace if necessary		•	•
Dust and Pollen Filter – replace		•	•
 Spark Plugs – replace at 35,000 miles or 3 years, whichever occurs first. Thereafter, every 40,000 miles or 3 years, whichever occurs first. – replace at 55,000 miles or 6 years, whichever occurs first. Thereafter, every 60,000 miles or 6 years, whichever occurs first. 		55K only: except A4, A5 and TTS with 2.0L TFSI engine	A4, A5 and TTS with 2.0L TFSI engine only
Power Steering Fluid – check, add if necessary			•
Air Cleaner – clean housing, replace filter element		55K only: except Audi Q7 4.2L	75K only: Audi Q7 4.2L only
Ribbed V Belt and Tensioner – check condition and replace if necessary		R8 only	Audi Q7 3.6L, R8 only
Ribbed V Belt – check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary.			 75K only: V6 FSI, V6 TFSI (rear be 2.0L TFSI, 5.2L V10 FSI, 4.2L V8 FSI only
 replace only the V belt for the compressor drive 			75K only: 3.0L TFSI only
Snow Screen for Air Cleaner – clean		A4, S4, A5, S5 and A6 only	A4, S4, A5, S5 and A6 only
Fuel Filter – remove water		Audi Q7 3.0L TDI only	
– replace		A3 2.0L TDI only	Audi Q7 3.0L TDI and A3 2.0L TDI only
Diesel Particulate Filter (DPF) – check ash loading according to manufacturer's work procedure, replace* if necessary.	 USA: 125K only: Audi Q7 3.0L TDI, A3 2.0L TDI only Canada: 200,000 km only: Audi Q7 3.0L TDI, A3 2.0L TDI only 		
Plenum Panel – remove cover for plenum panel to check water drain and :lean if necessary		except A3, Audi Q5	except A3, Audi Q5
irres and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS)	•		
 check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS) 		•	•
Fires – rotate, reset TPMS	5K only		
Niper Blades – check condition and replace if necessary	•	•	•
Niper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary	•	•	•
ights – check all lights, check headlight adjustment		A8 only	A3, A6, S6, A8 only
ights – check all lights via instrument cluster. Check license plate light from he rear of the vehicle			 Audi Q7, A4, S4, Audi Q5, TT, A5, S5, R8 only
i nterior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			•
Doors – lubricate doors, check straps and hood latch		A8 only	Except A8
Rear Lid Hinges – lubricate		A8 only	A8 only
Service Reminder Display – reset	•	•	•
lorn – check function		•	•
Brake System – check for damage, leaks, pad thickness, fluid level	•	•	•
Brake Discs – check thickness			•
xhaust System – check for damage, leaks		•	•
Front and Rear Axle – check for excessive play, check dust seals on ball joints and tie rod ends		A3, A6, S6, A8 only	•
Drive Shaft Boots – check		•	•
Automatic Transmission and Final Drive – check for leaks		•	•
Manual Transmission and Final Drive – check for leaks		•	•
Continuously Variable Transmission (multitronic) – change ATF			•
Haldex Clutch – change oil			A3, TT only
DSG/S Tronic – change oil and replace filter element			A3, TT only
– change oil			S4, S5 only
Jnderbody – check for damage and leaks		•	•
Road Test – check braking, kick-down, steering, electrical, heating and ventilation systems, air conditioning, ASL Automatic Shift Lock, power accessories and reset driver information display		•	•
Fiming Belt – replace at 110K miles (175,000 km) on Audi TTS or 130K miles (205,000 km) on Aud oulleys and replace if necessary. Brake Fluid – replace every 2 years regardless of mileage.	i A3 2.0L TDI only. Check condition of	timing belt tensioning system, o	lampening pulleys, and idler

Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.