



2014 MY Scheduled Maintenance Intervals

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95/135	35/75/115
(ilometers (in thousands)	8/40/70/100/130/160/190	25/85/145/205	55/115/175
Engine Oil/Oil Filter – change oil and replace filter	•	•	•
AdBlue Fluid - fill completely with fresh fluid (maximum capacity: 24 liters) and adapt	 05 3.0L TDI. A6 3.0L TDI and A7 3.0L 	05 3.0L TDI. A6 3.0L TDI and A7 3.0L	 Q5 3.0L TDI, A6 3.0L TDI and A7 3.0 TDI, Q7 3.0L TDI and A8 3.0L TDI onl
earned values for AdBlue tank under guided fault finding after filling fluid	TDI, Q7 3.0L TDI and A8 3.0L TDI only	TDI, Q7 3.0L TDI and A8 3.0L TDI only	TDI, Q7 3.0L TDI and A8 3.0L TDI on
Cooling System – check level, add if necessary		•	•
Engine Compartment – check for leaks		•	•
Onboard Diagnosis – check	Flex Fuel vehicles only	Flex Fuel vehicles only	Flex Fuel vehicles only
/isual Check – check the chassis for possible paint damage and corrosion, from the nside and outside, with the doors as well as hood and trunk lids open		•	•
Battery – check for clean terminals (no corrosion), properly mounted housing, and no damage; replace if necessary. Also, check the acid level of battery only if the level can be seen through the housing and fill if necessary		except Q5 hybrid	except Q5 hybrid
Small (12-volt) Side Battery – located in the trunk compartment on left side – check for clean terminals (no corrosion), properly mounted housing and no damage; replace f necessary		Q5 hybrid only	Q5 hybrid only
Oust and Pollen Filter – replace		•	•
Spark Plugs – replace at 35,000 miles (55,000 km) or 6 years, whichever occurs first. Thereafter, every 40,000 miles (60,000 km) or 6 years, whichever occurs first*			 all vehicles with the 4.0L V8 TFSI, A8 W12, all vehicles with 2.0L TFSI (except Flex Fuel engines)
 replace at 55,000 miles (85,000 km) or 6 years, whichever occurs first. Thereafter, every 60,000 miles (90,000 km) or 6 years, whichever occurs first 		 55K only: vehicles with the 3.0L V6 TFSI, 4.2L V8 FSI and 5.2L V10 FSI engines 	
 replace at 35,000 miles (55,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first 			 35K only: 2.0L TFSI Flex Fuel engines only
Power Steering Fluid – check, add if necessary			A8, Q7 only
Air Cleaner – clean housing, replace filter element		55K only: except RS 5, S6, S7, RS 7, A8 3.0L V6 TFSI, A8 3.0L V6 TDI,	RS 5, S6, S7, A8 3.0L V6 TDI, A8 3.0 V6 TFSI, A8 4.0L V8 TFSI, TTS and
– clean housing, replace filter element		A8 4.0L V8 TFSI and TTS RS 5 only	RS 7 only
Ribbed V Belt and Tensioner – check condition and replace if necessary		R8 Coupe, R8 Spyder only	R8 Coupe, R8 Spyder only
Ribbed V Belt – check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary – replace only the belt for the compressor drive (front belt)		O FFK solved which a with the	75K only
reptace only the bett for the compressor drive (front bett)		55K only: all vehicles with the 3.0L V6 TFSI	 115K only: all vehicles with the 3.0L V6 TFSI
Snow Screen for Air Cleaner – clean		A4, S4, allroad, A5, A5 Cabriolet, S5, S5 Cabriolet, Q5, SQ5 and Q5 hybrid only	 A4, S4, allroad, A5, A5 Cabriolet, S5, S5 Cabriolet, Q5, SQ5 and Q5 hybrid only
Fuel Filter – replace		A6 3.0L TDI, A7 3.0L TDI, A8 3.0L TDI, Q5 3.0L TDI and Q7 3.0L TDI only	 A6 3.0L TDI, A7 3.0L TDI, A8 3.0L T Q5 3.0L TDI and Q7 3.0L TDI only
Diesel Particulate Filter (DPF) – perform after the first 115K miles (USA)/175,000 km (Canada) or 110K miles (USA)/165,000 km (Canada) after a Diesel Particulate Filter (DPF) eplacement; check ash loading according to manufacturer's work procedure, replace** f necessary	USA: 115K only: A6 3.0L TDI, A7 3.0L TDI, A8 3.0L TDI, A9 3.0L TDI and Q7 3.0L TDI Canada: 175 km only: A6 3.0L TDI, A7 3.0L TDI, A8 3.0L TDI, Q5 3.0L TDI, Q5 3.0L TDI, Q5 3.0L TDI A9 3.0L TDI A9 3.0L TDI A9 3.0L TDI A		
Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary		•	•
Fires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS)	•		
 check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS) 		•	•
Fires – rotate, reset TPMS	SK only		
Niper Blades – check condition and replace if necessary (USA only)	•	•	•
Niper Blades – check condition (Canada only)	•	•	•
Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary	•	•	•
Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			•
Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights		•	•
Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights		•	•
Service Reminder Display – reset	•	•	•
Horn - check function		0	
		Q7, TT, TTS, R8 Coupe and R8 Spyder only	
Horn – check function		Q7, TT, TTS, R8 Coupe and R8 Spyder only	•





2014 MY Scheduled Maintenance Intervals (continued)

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95/135	35/75/115
Kilometers (in thousands)	8/40/70/100/130/160/190	25/85/145/205	55/115/175
All Sunroof Systems – clean guide rails and lubricate with grease		•	•
Front Latch for Cabriolet Roof – lubricate		 A5 Cabriolet and S5 Cabriolet only 	A5 Cabriolet and S5 Cabriolet only
Brake System – check for damage, leaks, pad thickness, fluid level	•	•	•
Brake Discs – check thickness			•
Exhaust System – check for damage, leaks		•	•
Front and Rear Axle – check for excessive play, check dust seals on ball joints and tie rod ends		•	•
Drive Shaft Boots - check		•	•
Automatic Transmission and Final Drive - check for leaks		•	•
Manual Transmission and Final Drive – check for leaks		•	•
Continuously Variable Transmission (multitronic) – change ATF			•
DSG/S Tronic® – change MTF oil for gear box		RS 5 only	RS 5 only
DSG/S Tronic – change ATF oil and replace transmission filter element for clutch hydraulics			S4, S5, S5 Cabriolet, S6, S7, RS 5, TT, TTS, R8 Coupe and R8 Spyder
Tiptronic Gear Box – change ATF			Q5 hybrid only
Rear Sport Differential – change ATF for clutch hydraulics and differential oil			RS 5 and RS 7 only
Underbody – check for damage and leaks		•	•
Road Test – check engine performance, clutch, manual/automatic transmission, braking (including hand and foot brake), steering, wheels, wheel bearings, drive shaft, horn and hybrid vehicles (electric drive for operational readiness)		•	•

Timing Belt - replace at 110K miles (175,000 km) on TTS. Check condition of timing belt tensioning system, dampening pulleys and idler pulleys, and replace if necessary

Brake Fluid - replace every 2 years regardless of mileage

Cloth Top – check function and rollover protection every 2 years regardless of mileage (A5/S5 Cabriolet and R8 Spyder only)

AdBlue Fluid – replace every 4 years regardless of miles/kilometers only if AdBlue has not been filled within the last 4 years (Q7 3.0L TDI, A8 3.0L TDI, A6 3.0L TDI, A7 3.0L TDI and Q5 3.0L TDI only)

Crash Active Headrest – check function every 2 years regardless of miles/kilometers (A8 only)

Haldex Clutch – change oil every 3 years regardless of mileage/kilometers (TT and TTS only)

*Does not include 2.0L TFSI Flex Fuel engines.

Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.

^{**}If DPF replacement is not necessary, perform check every 20,000 miles (30,000 km) thereafter until replacement becomes necessary. Subsequent DPF replacement interval is a minimum of 120,000 miles (195,000 km) thereafter.